

# THE TIGER T ocean



EPS fish boxes



EPS 6, AIRPOP, STYROFOAM®

Compactor System, Type	TIGER 130 T ocean	TIGER 200 T ocean
Capacity <sup>1)</sup>	up to 15 kg/h	up to 60 kg/h
Achievable compaction <sup>1)</sup>	up to 250 kg/m <sup>3</sup>	up to 350 kg/m <sup>3</sup>
Processible material densities	up to 25 g/l	up to 25 g/l
Processible height of foamed part	up to 300 mm	up to 350 mm
Actual charging opening (W x D)	700 x 360 mm	800 x 500 mm
Block dimensions	130 x 130 mm	210 x 210 mm
Assembly dimensions (L x D x H)	2.800 x 450 x 1.600 mm	3.800 x 650 x 1.700 mm
Machine weight	310 kg	650 kg
Electrical connection	1,5 kW	5,5 kW
Supply voltage (EU)	3 x 230 V 50 Hz / 3 x 400 V 50 Hz	3 x 400 V 50 Hz
Supply voltage (USA)	3 x 230 V 60 Hz / 3 x 480 V 60 Hz	3 x 480 V 60 Hz
Marking	CE	CE
Remarks	Machine version in corrosion-resistant design	

<sup>1)</sup> depending on material type and material density

Subject to change without notice / No responsibility is taken for the correctness information